

			
Series		G2H15*****	
Design		Turbine	
Housing		Stainless Steel	
Fitting Size	Option 1	1-1/2 inch	
Fitting Type	Option 1	NPT	
	Option 2	ISO	
Flow Range	GPM	10-100 GPM	
	LPM	38-380 LPM	
Accuracy		+-1% of reading	
Repeatability		+- .1%	
Pressure Rating	PSIG	3000 PSIG	
	bar	207 bar	
Operating Temperature Range	Fahrenheit	14 to 140°F	
	Celsius	-10 to 60°C	
Typical K Factor		210	
Wetted Components	Housing	316 SS	
	Journal Bearings	Ceramic	
	Shaft	Tungsten Carbide	
	Rotor	PVDF (Kynar)	
	Rings	316 SS	
Frequency Range		35-350 Hz @ 10-100 GPM	
Strainer Size		55 mesh	
Maximum Flow	GPM	150 GPM	
	LPM	568 LPM	
Maximum Pressure Drop in 10:1 Range	PSIG	4 PSIG	
	bar	0.28 bar	
Wrench Flat Size	Inch	3/8 inch	
	mm	60 mm	
Weight - Turbine Only	lbs	4 lbs	
	kg	1.8 kg	
Weight - Turbine with Computer	lbs	4.2 lbs	
	kg	1.9 kg	
Shipping Weight - Turbine Only	lbs	4.4 lbs	
	kg	2 kg	
Shipping Weight - Turbine with Computer	lbs	4.6 lbs	
	kg	2.1 kg	
Electronic Features	Feature 1	2 Totals(1 Resettable/1 Cumulative)	
	Feature 2	Factory Cal in Gal or Litre	
	Feature 3	2 User Calibrations and Flowrate	